


Requested Patent: EP0893758A2
Title: DETACHABLE JAVA APPLETS ;
Abstracted Patent: EP0893758 ;
Publication Date: 1999-01-27 ;
Inventor(s): RAZAVI BEHFAR (US); HARSHBARGER ERIC (US) ;
Applicant(s): SUN MICROSYSTEMS INC (US) ;
Application Number: EP19980305935 19980724 ;
Priority Number(s): US19970910481 19970725 ;
IPC Classification: G06F9/44 ;
Equivalents: CN1208889, JP11167489

ABSTRACT:

A method and system is disclosed for detaching Java applets from the constraints of the application such as a browser which provides the Java engine for executing those applets. Thus, the applets, when detached, can appear in a detached window which is more easily controllable by the operating environment desktop. The Java applets continue to run under the application's virtual machine but do so without regard to the graphical interface limits of the application. Further, if the application that launched the applet proceeds to a new URL location, the Java applet continues to run. Also, the applet, once detached, can be reattached into the application to appear in the application history.



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) EP 0 893 758 A2

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:
27.01.1999 Bulletin 1999/04

(51) Int Cl.⁶ G06F 9/44

(21) Application number: 98305935.3

(22) Date of filing: 24.07.1998

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE
Designated Extension States:
AL LT LV MK RO SI

(72) Inventors:
• Razavi, Behfar
San Jose, California 95123 (US)
• Marshbarger, Eric
San Francisco, California 94132 (US)

(30) Priority: 25.07.1997 US 910481

(74) Representative: Foster, Mark Charles et al
Edward Evans & Co.,
Chancery House,
53-64 Chancery Lane
London WC2A 1SD (GB)

(71) Applicant: Sun Microsystems, Inc.
Palo Alto, California 94303-4900 (US)

(54) Detachable java applets

(57) A method and system is disclosed for detaching Java applets from the constraints of the application such as a browser which provides the Java engine for executing those applets. Thus, the applets, when detached, can appear in a detached window which is more easily controllable by the operating environment desktop. The

Java applets continue to run under the application's virtual machine but do so without regard to the graphical interface limits of the application. Further, if the application that launched the applet proceeds to a new URL location, the Java applet continues to run. Also, the applet, once detached, can be reattached into the application to appear in the application history.




FIGURE 2

Description

The present invention relates to the field of computer software. More specifically, the present invention relates to applets and their relationship to an operating environment.

Description of Related Art

Recent versions of applications such as browsers like Netscape Navigator 3.0™ or Hot Java™ (a product of Sun Microsystems, the Sun logo and Hot Java are trademarks or registered trademarks of Sun Microsystems in the United States and other countries) have provided for the use of platform-independent "applets" which can be downloaded as pre-compiled Java byte-codes (intermediate level instructions). These applets are executed via a "virtual machine," which is a platform-specific environment that interprets or compiles the applet code and performs the high-level instructions therein. One popular and predominant applet programming language, developed by Sun Microsystems, Inc., is known as "Java™" (a product of Sun Microsystems, the Sun logo and Java are trademarks or registered trademarks of Sun Microsystems in the United States and other countries). Applets programmed in Java or minor variations thereof are referred to as Java applets.

The key usefulness of Java applets is that they are platform-independent, i.e., a Java applet written for platform A will run without modification on platform B provided that both platform A and platform B have virtual machines capable of executing applet code for their respective platforms. Even though Java applets are platform-independent, the characteristics, quirks and limitations of the applications from which they are spawned weaken the flexibility by causing the applets to become essentially "application-dependent." For example, one limitation of Java applets when called from HTML (Hypertext Markup Language) code for the Sun operating system version of Netscape Navigator is that when applets are called, the HTML tag for the call must include a height and width, thus defining a window size that the applet must execute within. When running inside the application window, the applet is constrained by the stated height and width tag and thus, any output, input, dialog boxes or pop-up windows that are generated for the applet must appear within that constraint.

In this situation, where the applet window is a "sub-window" of the application window, the applet window suffers several impediments. First, the applet window cannot be closed unless the application is quit or until the application transitions to receive data from a new host (in the same window that launched (spawned) the applet). And concomitant with that limitation, when the application that spawned the applet transitions to a new URL (Uniform Resource Locator--the "address" of the host visited by the application) then the applet window closes and the applet ceases execution. The cessation of the applet is out of the control of the user. In certain instances, it is desirable to continue running the applet even though the application has transitioned to a different URL. For instance, a user may desire a streaming audio applet that plays content from an external or remote source which is launched from URL A to continue playing even though the application has proceeded to URL B, which does not have the same applet. Under current practice, it would be necessary to open or spawn a new instance of the application (i.e., open a new application window) to receive its content from URL B so that the other application instance continues to play the audio applet. But this approach suffers from several maladies.

First, launching a new application instance may involve an increase in memory and system resource utilization which will diminish the performance of both the applet and the new application instance. Further, the applet still cannot be controlled outside of the constraints or environment of the application. In fact, with a second application window (instance) launched, the first window must become active (in the foreground, under control of cursor or mouse) before the applet can be controlled. Further, the traditional applet model does not allow for iconification of the applet window within the operating environment (minimizing of the window). Under current practice, the application window itself must be minimized in order to minimize and iconify the applet. In that case, the applet rather than having its own icon, will inherit the icon of the browser. The lack of window minimization, resizing and other GUI modification such as changing fonts, backgrounds colors, etc., imposes severe constraints on the applet to be independently controlled without application constraints.

One solution to remove the application dependence of executable code modules has been the use of "plug-ins". However, unlike "plug-ins" (file(s) containing data/code used to alter, enhance, or extend the operation of a parent application) that are operating environment/platform specific, Java applets are essentially platform independent. Plug-ins, which must be downloaded (or come packaged with the application), allow certain file types (such as ShockWave™ or RealAudio™) which may not be supported internally by the application to be interpreted and output on the local platform. However, plug-ins are disadvantageous in that they remain resident locally and must be stored on local disk for re-use, unlike the virtual machine of Java which is application resident. Importantly, plug-ins spawn processes wholly independent of the browser and are thus, platform dependent. Thus, though plug-ins may allow for independent GUI control of their windows, they are completely disinherited from the browser unlike Java applets (because they do not require a virtual machine to run). Running a plug-in is akin to running a separate application via the operating environ-

ment, and thus is not a viable substitute for portable executability as is a Java applet.

Yet another development for enhancing capabilities of an application such as a browser is the use of "helper" applications. Helper applications, which are stored locally, do not have the portability and platform independence of Java applets, i.e., a helper application on a Pentium platform cannot be used on a Sun Sparc™ (a product of Sun Microsystems, the Sun logo and Sparc are trademarks or registered trademarks of Sun Microsystems in the United States and other countries) system or vice-versa. The helper application also spawns a new process/thread within the operating environment and commands the system resources of a new application instance which is unlike Java applets. The helper application is not related to the application delivering the data to be processed and is merely called through the operating environment. The helper application does not plug-in or execute within a virtual machine of the application. Further, a helper application is not easily transferred from host to client, since helper applications can be quite large in code size when compared to applets.

Further, on newer information devices such as network computers (NCs), helper applications and plug-ins may not even work due to limited operating environment features and lack of local storage. NCs are conceptually based on utilizing remotely stored applets, such as Java applets which are network distributed, to provide applications and content to the NC. In contrast, the current industry standard or NCs guarantees that NCs are able to execute Java applets, through the use of virtual machine and browser/application. Even in the NC situation, it is desirable that the applet have its own built-in functionality separate from the browser/application from which it is called.

Thus, there is a need for a method and apparatus to detach Java applets from the constraints of the application so that they can be GUI-controlled directly through the operating environment and so that they not be limited by the state of the application in which the applets are spawned.

SUMMARY

A method and system is disclosed for detaching Java applets from the constraints of the application which provides the Java virtual machine for executing those applets. Thus, the applets, when detached, can appear in a detached window which is more easily controllable by the operating environment desktop. The Java applets continue to run under the application's virtual machine but do so with less constraints than the graphical interface limits of the application. Further, if the application that launched the applet transitions to a new URL host, the Java applet continues to run. Also, the applet, once detached, can be reattached into the application to appear in an application history.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is a flow diagram of transforming a non-detachable Java applet to have the functionality of detachability according to an embodiment of the invention.

Figure 2 illustrates a flow diagram of applet behavior when Launched from an application according to an embodiment of the invention.

Figure 3 is a diagram of exemplary inheritance hierarchy as defined for Java applets.

Figure 4 is an illustration of a resulting detached applet as rendered on a display screen.

Figure 5 shows an applet "Jukebox" in the attached state.

Figure 6 is a flow diagram of the detaching of an applet according to one embodiment of the invention.

Figure 7 is a flow diagram of the attaching of an applet according to one embodiment of the invention.

DETAILED DESCRIPTION OF THE INVENTION

Definitions

The word "operating environment" refers to an operating system, kernel, shell, or the like which is low-level software which schedules tasks, allocates storage, handles the interface to peripheral hardware and presents a default interface to the user when no application program is running. The operating environment also allows application programs to run by performing storage allocation, input/output, etc., that the application may request through its executable code.

The word "desktop" refers to the visual environment (usually output on a display screen) wherein the operating environment allows a user to interact with the operating environment. A desktop includes but is not limited to the display and use of icons, cursors, windows, dialog boxes, menus and other user interface elements which are a function of the operating environment. The desktop is a visually rendered screen region wherein application windows and their associated input/output may be displayed and interacted upon by a user, if desired.

A "method" as used in the detailed description refers to a function call, procedure or routine associated with one or more classes, which are well-known in the art of object-oriented programming.

The word "detachable" refers to the ability of an applet to become free of GUI constraints imposed upon it by the

application that spawned the applet. "Detachability" implies that the applet is capable of being manipulated in a graphical user interface sense separate of the application that spawned it and can instead be manipulated on the desktop by interaction directly with the operating environment.

5 The word "virtual machine" refers to an interpreter, compiler, linker, etc., which is included in an application or operating environment to facilitate the execution of instructions, pseudo-code and the like for a particular programming language such as Java.

Figure 1 is a flow diagram of transforming a non-detachable Java applet to have the functionality of detachability according to an embodiment of the invention.

10 Any pre-existing Java applet can be modified to become a detachable Java applet as detachable is described with respect to various embodiments of the invention. When an applet is defined/created, its source code can be modified to include methods for detaching the applet. The first step is to add an "implements Detachable" statement to the class definition of the applet (step 110). This implements an interface called "Detachable". Appendix A, the Java source code for the Jukebox streaming audio applet, shows on column 2, the class definition "public class Jukebox extends Applet implements Detachable." The phrase "public class <Applet Name> extends Applet" is shared by all applets in their
15 main class definition. The phrase "implements Detachable" may then be appended to any such definition to begin the modification of the <Applet Name> applet to become detachable. Several more steps are desirable in order to complete the foundation for detachability of the applet. The Detachable interface invoked via the class definition is implemented by adding several generic "methods" (see Definitions, above) to the source code of the applet (step 120). The methods while generic in terms of the Detachable interface are peculiar and unique to this embodiment of the invention in that
20 these methods have not been previously defined in the art of Java development.

The generic methods will allow a Java applet to become detachable from the application in which they were spawned and will allow the applet to have the functionality of any ordinary application window running on the operating environment (e.g., Solaris™, a product of Sun Microsystems, Solaris is a trademark or registered trademark of Sun Microsystems in the U.S. and foreign countries) desktop. The generic methods, if they are not adequate for that specific
25 applet's look-and-feel (checked at step 130), may be modified. The generic methods can be modified to include interfacing that suits the look-and-feel or peculiarities of the applet (step 140). For example, it may be desired in a detachable "chat" (text-based conversation between users) applet that the chat window resize itself to display long strings of text which without resizing itself were invisible. The methods, which are defined below may be modified by one of ordinary skill in the art to suit the applet being transformed into a detachable applet. One such modification, described below,
30 is the addition of "controller" methods. As described with respect to step 120, these generic methods are added to the exemplary Jukebox applet code disclosed in Appendix A.

Generic Detachable Interface Methods and Modifications Thereto

35 1. "Detach" (illustrated as "public void detach () {" in Appendix A).

The Detach method is the primary function call allowing the applet to be detached from the application. The state variable "isDetached" is set equal to true to indicate the applet is now in the detached as opposed to attached state. The statement "remove(Ulpanel)" is responsible for removing the "panel" for the user interface which contains components like user interface elements (i.e., buttons, text boxes, menus, icons, etc.). The panel Ulpanel is removed and
40 passed onto the "Detached Frame" class that is instantiated. The "Detached Frame" class is a platform-independent implementation based on the standard Java virtual machine and is thus available to all Java platforms. Code for the Detached Frame class is shown in Appendix B. The Detached Frame is instantiated to create a detached window (application independent applet window) into which Ulpanel components (user interface elements) can be rendered.
45 The statement "controller.makeAttachable()," is an example of a modification of the generic Detach method that is specific to the Jukebox applet that creates a user interface element for attaching the applet back to the application.

2. "Attach" (illustrated as "public void attach () {" in Appendix A)

50 The Attach method is used to re-attach the applet back to the application and to close the detached window residing outside of the application's window. The state of the applet is returned to attached by setting isDetached equal to false. Next, the Detached Frame object is disposed of. The Ulpanel components are then added back to the application (add (Ulpanel) statement). An example of applet-specific (in this case, the Jukebox applet) modification to the generic method Attach is the controller.makeAttachable statement which when included provides user interface elements for
55 detaching out the applet.

3. Close (illustrated as "public void close()" in Appendix A)

The Close method kills the Detached Frame window and typically, the applet does not thereafter re-attach to the application. This method is useful when total purging of the applet is desired.

5 These generic methods, when added to implement the Detachable interface, will cause a non-detachable applet to become detachable (have the functionality of detaching from the application window).

Figure 2 illustrates a flow diagram of applet behavior when launched from an application according to an embodiment of the invention.

10 Though Figure 2 is directed toward detaching from a application, the methodology is equally applicable to detaching applets from any environment that executes the applet code through a virtual machine.

According to step 210, first, the applet must be launched in the virtual machine of the application. This is usually accomplished automatically when a user visit a web site (HTML page) which includes statement for launching the applet. Assuming that the applet as been transformed according to the methodology of Figure 1, or if the applet is already capable of detaching, the virtual machine is checking (waiting) for the user to activate the user element, such as a button, to detach the applet from the application (checked at step 220). If the user has activated the "detach" user interface element, then the environment calls the "Detach" method (step 230).

20 The calling of the "Decach" method, for example, leads to the execution of other instructions as mentioned above. One key result of these instructions is the displaying of a detached window in which the applet controls and perhaps, data would be rendered on to (step 240). Two checks are continuously being performed once the display has rendered the detached window. The first is to see whether the user changed properties (such as size, background color, etc.) of the detached window (step 255). This step is a check performed not from the application, but from the operating environment itself. If any changes are requested of the properties of the detached window, the operating environment initiates and completes those changed properties (step 250). Such changes include resizing the detaching window, changing the fonts of the window, and since the detached window is a window of the operating environment, minimizing and iconification can be performed without reference, modification of the application window. Further, the applet in the detached window is no longer application constrained, and has its own set of graphical properties--color, background, font, size, etc.--apart from the application. The desktop can control the look-and-feel of the detached window, and consequently, to some degree, the applet as well.

30 The second check being performed is to query if the user activated the user interface element to attach the applet back to application (step 260). Once the applet is in the Detached Frame, the user interface element (button, etc.) for detaching will be replaced by a user interface element for attaching the applet back to the application. A request by the user to attach the applet to the application will first cause the "Attach" method to be called (step 270). The Attach method includes several instructions as described above but has the primary functionality of closing the detached window (step 280) and removing it from the operating environment. The applet is then redrawn into the application window as when the applet was launched maintaining not the detached look-and-feel, but reverting to the look-and-feel of the application which launched the applet. The applet, when redrawn into the application will replace the user interface element for attach with the user interface element for detach. Thus, the applet can switch states from attached to detached as the user so desires. Not shown in Figure 2 is the case where the application has transitioned to a new host prior to the applet being attached. In that case, the applet, rather than being redrawn in the application window, becomes part of the application's "history". The history is a record of previously visited URLs so that users of the application can return to those URL sites again.

Figure 3 is a diagram of exemplary inheritance hierarchy as defined for Java applets.

45 From object or class inheritance viewpoint, there are two sets of inheritance trees for the various embodiments of the invention. The first, shown on the right-hand side of Figure 3 is the generic Java applet inheritance hierarchy. An Object 310 is inherited into a Component 320. The Component 320 (and consequently Object 310) is inherited into Container 330. Container 330 is inherited into Panel 340. Finally, Panel 340 is inherited into Applet 350.

The second hierarchy shown in Figure 3 is the hierarchy created by inheritance of the Detached Frame. This hierarchy is a representation of the methodology of detaching an applet described with respect to various embodiments of the invention.

50 Like the generic applet inheritance hierarchy, the left side of Figure 3, the Detached Frame inheritance hierarchy shows an Object 315 inherited into a Component 325. A Container 335 is, likewise, inherited into a Container 335. Figure 3 shows that the two hierarchies are identical up to and including the Container object. Thus, the hierarchies may be joined at Containers 335 and 330. The joining of the inheritance hierarchy is conceptually the object-oriented mechanism allowing an Applet 350 to be transferred from the application window to the detached frame since both are instances of class container. One skilled in the art of object-oriented programming will readily be able to utilize the property of joined object hierarchies described above to implement the various embodiments of the invention.

Figure 4 is an illustration of a resulting detached applet as rendered on a display screen.

Figure 4 shows a display 400 which may any monitor, display or other visual device that renders a application

window 410 through the operating environment. Application window 410 is shown as an application window which contains several elements such as a picture and URL (Uniform Resource Location) (labeled as "location"), but may be any window or display environment running over the operating environment. Display 400 shows the application window 410 running over an operating environment desktop 430 (see above for definition of "desktop"). The operating environment desktop 430 and application window 410 may be more intimately or tightly integrated such as in Hot Java Views™ (a product of Sun Microsystems, the Sun logo and Hot Java Views are trademarks or registered trademarks of Sun Microsystems in the United States and other countries). The invention can be modified as to remove any lingering visual and user interface constraints of the application window which may restrain an applet however tightly integrated the application and environment may seem. In this sense, Figure 4 shows an applet named "Jukebox" in a detached window 420. The applet was launched at some URL location and initially, contained within application window 410 (see Figure 5). Figure 4 shows the detached state of the applet Jukebox.

In this detached state, the applet controls "About", "Stop" and "Play" are rendered into the detached window. An important aspect to the invention is the ability of the applet to continue running or executing its instructions under the virtual machine (interpreter) of the application whose window is rendered in 410. The operating environment and its desktop 430 now controls the general look-and-feel of the window for the applet Jukebox. The detached window can then be manipulated like any other window on the desktop. The application window 410 and the interface properties of the application no longer control, constrain or limit the GUI characteristics of the applet. Further, when the application window 410 transitions to a new host URL, the applet continues to run in the Detached Frame. Though the virtual machine is platform-dependent, i.e., it must decompose Java code into processor/platform native code, the Java applet and its code is not. When the application closes all of its windows completely, the detached applet is closed as it should be. Further, the applet, even though detached, must cease execution because it is no longer streaming data from the host that was contacted by the application. Thus, the application retains control of concurrently terminating the applet when terminating itself even though the applet is detached from its windowing and interface constraints of the application window.

While in the detached state, several other GUI modifications are available to the detached window which are not explicitly illustrated. First, unlike traditional applets, a detached window 420 can be iconified onto an area of the desktop 430 or minimized into a toolbar or other GUI element without having to iconify the application window 410 as well. Thus, the minimized applet can have its own icon. Further, the detached window 420 may be resized on the desktop 430 while in the detached state without reference to the height-width tag within the HTML (Hypertext Markup Language) or other document which specified the calling of the applet from within the application window 410. This allows the detached applet greater flexibility in its appearance than the non-detachable applet. Further modifications such as a change of font type, font size, color, background, etc., that are available to other windows running on desktop 430 are also available for the detached window 420 and the applet it displays.

The detached window 420 contains, in addition to applet control for the Jukebox, a "control" (a user interface element) is rendered called "Attach" which, when activated, will close the detached window 420 and collapse the applet back into application window 410. This "Attached" state is shown in Figure 5. If application window had transitioned to a new host URL, then the applet is included in the application history instead of being instantly executed in the application window.

Figure 5 shows an applet "Jukebox" in the attached state.

Figure 5 also has a display device 500, an operating environment desktop 530 and a application window 510. When an applet is in the attached state, the application window 410 constrains it. However, if the applet has been made detachable, a "detach" control (button) is rendered into the application window in the panel of the applet so that the attached state may be modified to the detached state leading to a detached window as shown in Figure 4. Alternatively, the applet can be launched automatically into the detached state with a control for attaching as shown in Figure 4. A "toggle" method can also be provided to toggle the state of the applet regardless of what the current state is. The toggle can be initiated by a user interface element in both the detached window when the applet is in the detached state and the applet panel (in the application window) when the applet is in the attached state. The toggle method may be desirable where a uniform control is desired in both attached and detached states. The attached state shown in Figure 5 is unlike the prior art since the applet shown is "detachable" via the "detach control." An applet without detachability would be limited to the application itself and users would be unable to change the display properties of the applet Panel 550 in the application window 510. A detachable applet in the attached state suffers the same limitation, but can be freed by activating "Detach." The attached applet state of Figure 5 assures that prior to being re-attached from a "detached" state (shown in Figure 4), the host URL of the application window 510 had not changed.

Figure 6 is a flow diagram of the detaching of an applet according to one embodiment of the invention.

The method definition of "Detach" described above with respect to code Appendix A is not fully represented in Figure 6 but it will be understood by one skilled in the art that any additional steps shown or omitted from the method definition can easily be implemented.

The first step in detaching is to instantiate a new frame called Detached Frame (see Figure 1 description of Detach

method) (step 610). The new frame is then used as a drop-off point for applet data, content and user interface elements/controls. Next, the applet components are removed from the application applet panel (step 620). These components are objects including, but not limited to, buttons, controls, user interface elements, action messages, dialog boxes, data, etc., which may be renderable to the display device. The applet components are then added to the user interface of the new frame (step 630). Additionally, an "attach" user interface element is added to the new frame in addition to other components so that the applet may re-attach to the application (step 640). Next, the detached window generated through the new frame is mapped or rendered on the display device (step 645). The detached window is, at this stage of the process, a blank window capable of interfacing within the desktop environment of the operating environment. As implemented in various embodiments of the invention, the detached window will inherit size, font, color characteristics of the applet panel as attached in the application window (step 655). Finally, the components, including the attach control, are painted on the screen using the "Paint All" Java method (step 660). The "Paint All" method, well-known in the art of Java programming, is used to render objects to the display or operating environment, rather than within a portion of the application window. This ensures that components for the detached applet will be properly rendered, i.e., without showing up as meshed with other screen graphics or as hidden from view.

Figure 7 is a flow diagram of the attaching of an applet according to one embodiment of the invention.

Again, though the flow diagram of Figure 7 may vary from the method "Attach" described earlier, one skilled in the art will readily be able to exchange/add features of that method into the flow diagram of Figure 7 and vice-versa.

When the attach control is activated, first the new frame instantiated by the calling of the Detach method is disposed from the virtual machine environment (step 710). Components which were removed from the application environment are added back to the application, and automatically rendered in a panel therein as with a typical Java applet (step 720). Next, the detached window is closed (step 730) or removed from the operating environment. Finally, garbage collection and reallocation of memory (step 740) may be allowed to recycle the resources utilized by the detached frame instantiated by the Detach method back to the operating environment.

While the present invention has been particularly described with reference to the various figures, it should be understood that the figures are for illustration only and should not be taken as limiting the scope of the invention. Many changes and modifications may be made to the invention, by one having ordinary skill in the art, without departing from the spirit and scope of the invention.

The processes described above may be performed by a computer program running on a computer in the embodiment described. Such a computer program can be recorded on a recording medium (for example a magnetic disc or tape, an optical disc or an electronic memory device, such as a ROM) in a way well known to those skilled in the art. When the recording medium is read by a suitable reading device, such as a magnetic or optical disc drive, a signal is produced which causes a computer to perform the processes described.

The processes may also be performed by electronic means.

APPENDIX A
Jukebox.java

```

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55

/**
 * Jukebox.java      11/30/95      Robert Masavi
 *
 * This Java Jukebox - a networked audio on demand applet.
 * It can run as either a standalone application or as an applet.
 * It can run in any of several modes:
 *
 * - net: networked streamed audio on demand
 * - live: networked streamed live audio
 * - liveurl: streamed live audio over a URL
 * - file: local audio files
 * - url: audio URL's
 * - stream: audio URL's with scrolling
 * - playlist: audio URL's with scrolling
 *
 * When in net or file mode, the jukebox creates vch-type controls
 * that allow the user to stop, play, or rewind the audio stream or
 * to jump to a different selection.
 *
 * In net mode, an image - the CD cover - is optionally associated
 * with each audio selection and is displayed while that selection
 * is playing. For each selection, the Jukebox opens a TCP connection
 * to the audio server for controlling the media. User commands are
 * relayed to the server over the TCP connection. Multiple audio
 * data flows back to the applet over UDP.
 *
 * The selection list, server, and port are provided as parameters
 * in the applet tag.
 *
 * In live mode, the user can only stop or start the stream and there
 * is no image.
 *
 * The Jukebox GUI consists of a media controller and a selection box.
 * The selection box displays the current selection and its associated
 * image if any. The controller provides vch-type controls for a
 * MediaPlayer object.
 *
 * Underneath, the actual work is done by a "connection graph" of
 * fine-grained multimedia objects. The Jukebox interacts with
 * MediaPlayer which may in turn be MediaPlayer or AudioClip layers.
 */
import java.awt.*;
import java.io.*;
import java.util.*;
import java.net.*;
import java.applet.*;
import sun.awt.*;

/* ===== */
class Jukebox
{
    // If the Jukebox is invoked as an applet, it accepts the following parameters:
    // the only mandatory parameter is the selection parameter which defines
    // the audio selection. The rest have reasonable defaults.
    //
    // selection - list of tracks and slides are in this format:
    //
    // audio_filename;image_filename;audio_filename;image_filename;...
    // or:
    // audio_filename;audio_filename;...
    //
    // depending on whether images should be displayed or not.
    //
    // conf - name of a configuration URL that contains all the
    // options below. The format of the config file is
    // optionsname = "value"
    //
    // server - name of server host (has to match documentbase name
    // to avoid security exceptions.)
    //
    // port - port number the audio server is listening on
    // foreground - applet foreground color
    // background - applet background color
    // fontname - applet font
    // fontstyle - applet font style
    // fontsize - applet font size
    // slidewidth - slide width
    // slideheight - slide height
    // slider - place where the slides reside on the server
    // sliderdir - place where the audio resides on the server
    // mediatype - one of:
    // net, live, liveurl, file, memory, stream, urlstream, or URL
    // (default is net)
    // showimage - true or false for whether to show the image
    //
    // If the Jukebox is invoked as an application, it expects to retrieve
    // all these parameters through a configuration URL using the same format
    // as the conf parameter above.
    //
    // The Jukebox can also be invoked with a list of audio files on the
    // command line, in which case it will assume that it is operating in
    // file mode and plays the local audio files.
    //
    // =====
    public class Jukebox extends Applet implements Detachable {
        // =====
        JukeboxSelection selbox; // controls the selection list
        JukeboxControl controller; // vch-type controls for the media
        JukeboxURL url; // place holder for UI components
        DetachableFrame detachFrame; // frame for holding detached Jukebox
        String trackList; // names of audio tracks
        String titleList; // corresponding titles
        Image background; // background image
        Image foreground; // foreground image
        boolean isAttached = false; // is the Jukebox detachable?
        boolean isDetachable; // is the Jukebox detachable?
        String sliderdir = null; // directory where media resides
        String selection = null; // directory where slides reside
        String foreground = null; // list of media files
        String background = null; // foreground color
        String fontName = null; // font name
        String fontStyle = null; // font style
        String fontSize = null; // font size
        String mediatype = null; // media type
        boolean showImage = true; // show image or not
        int slideHeight = 0; // slide height
        int slideWidth = 0; // slide width
        String server = null; // name of the audio server host
        URL docbase = null; // name of the server's base URL
        URL codebase = null; // name of the server's base URL
        int port = 0; // port
        final int JUKEDBOX_PORT = 13300; // default on-demand port
        final int LIVEAUDIO_PORT = 12000; // default live port
    }
}

```

```

5
10
15
20
25
30
35
40
45
50
55

// Jukebox.java
//
// Used when the Jukebox is invoked as an applet
//
public void init() {
    Jukebox.configure();
    codebase = getCodeBase();
    isDetachable = true;
    initialize();
}

// Used when the Jukebox is invoked as a standalone application
//
public static void main(String argv[]) {
    if (argv.length < 1) {
        System.out.println("Usage: java Jukebox <url>(<flags>);");
        System.exit(1);
    }
    Jukebox jukebox = new Jukebox();
    try {
        Jukebox.configure(argv[0]);
        Jukebox codebase = null;
        Jukebox URLConfig(Jukebox.configure(),
            (URL)URLConfig(Jukebox.configure(),
                for (int i = 0; i < argv.length; i++)
                    Jukebox.selection = argv[i] + "\n";
                Jukebox.appletType = "file";
                Jukebox.showslides = false;
            }
        Jukebox.isDetachable = false;
        Jukebox.initialize();
        new DetachedFrame("Java Jukebox", Jukebox,
            Jukebox.UIPanel, Jukebox.Iconing);
    }
}

// Get Jukebox parameters from the applet html tag
//
private void HTMLConfig() {
    // Get the server name and port number to connect to.
    //
    server = getParameter("server");
    try {
        port = Integer.parseInt(getParameter("port"));
    } catch (Exception e) {}
    //
    // Get selection list and associated image names
    // followed by appearance parameters
    //
    mediaDir = getParameter("mediaDir");
    alldir = getParameter("mediaType");
    alldir = getParameter("alldir");
    selection = getParameter("selection");
    foreground = getParameter("foreground");
    background = getParameter("background");
    fontName = getParameter("fontName");
    fontStyle = getParameter("fontStyle");
    if (getParameter("showslides") != null)
        showslides = getParameter("showslides").equals("true");
        fontsize = Integer.parseInt(getParameter("fontsize"));
        try {
            alldirHeight = Integer.parseInt(
                getParameter("alldirHeight"));
        } catch (Exception e) {}
        alldirWidth = Integer.parseInt(
            getParameter("alldirWidth"));
        try {
            alldirWidth = Integer.parseInt(
                getParameter("alldirWidth"));
        } catch (Exception e) {}
        // Configuration URL name
        if (config = getParameter("config") != null) {
            try {
                URLConfig(new URL(getDocumentBase(), config));
                System.out.println("Unable to resolve " + config);
                System.out.println("Jukebox not configured");
            } catch (Exception e) {}
        }
        // Get Jukebox parameters from a URL
        //
        private void URLConfig(URL configURL) {
            if (configURL == null)
                return;
            StringURLConfig t1, t2;
            String test = "";
            Hashtable params = new Hashtable();
            try {
                DataInputStream s;
                String inputLine;
                s = new DataInputStream(configURL.openStream());
                while ((inputLine = s.readLine()) != null) {
                    test = test + inputLine;
                }
                s.close();
            } catch (Exception e) {
                System.out.println("Error loading config URL: " + e);
                e.printStackTrace();
                return;
            }
            t1 = new StringTokenizer(test, "\n");
            while (t1.hasMoreTokens() > 0) {
                String arg = t1.nextToken();
                String value = t1.nextToken();
                t2 = new StringTokenizer(arg, "\n");
                String paramname = t2.nextToken();
                params.put(paramname, value);
            }
            if (params.containsKey("server"))
                server = (String)params.get("server");
            if (params.containsKey("port"))
                try {

```

APPENDIX A

Jukebox.java

```

5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55

    port = Integer.parseInt((String)params.get("port"));
    } catch (Exception e) {
        if (params.containsKey("mediadir"))
            mediadir = (String)params.get("mediadir");
        if (params.containsKey("mediatype"))
            mediatype = (String)params.get("mediatype");
        if (params.containsKey("slideshow"))
            slideshow = (String)params.get("slideshow");
        if (params.containsKey("showslides"))
            showslides = (String)params.get("showslides");
        if (params.containsKey("selection"))
            selection = (String)params.get("selection");
        if (params.containsKey("foreground"))
            foreground = (String)params.get("foreground");
        if (params.containsKey("background"))
            background = (String)params.get("background");
        if (params.containsKey("fontname"))
            fontname = (String)params.get("fontname");
        if (params.containsKey("fontstyle"))
            fontstyle = (String)params.get("fontstyle");
        if (params.containsKey("fontsize"))
            fontsize = Integer.parseInt(
                (String)params.get("fontsize"));
        if (params.containsKey("slideshow"))
            try {
                fontsize = Integer.parseInt(
                    (String)params.get("fontsize"));
            } catch (Exception e) {}
        if (params.containsKey("slideshow"))
            try {
                fontsize = Integer.parseInt(
                    (String)params.get("slideshow"));
            } catch (Exception e) {}
        if (params.containsKey("slideshow"))
            try {
                fontsize = Integer.parseInt(
                    (String)params.get("slideshow"));
            } catch (Exception e) {}
    }

    private void initialize() {
        String title = null;
        Toolkit tk = getToolkit();

        // Set some defaults for missing parameters
        //
        if (mediadir == null)
            mediadir = ".";
        if (mediatype == null)
            mediatype = "audio";
        if (slideshow == null)
            slideshow = "true";
        if (fontname == null)
            fontname = "TimesRoman";
        if (fontstyle == null)
            fontstyle = "plain";
        if (server == null)
            if (debug > 0)
                server = "localhost";
            else
                server = "localhost";
        if (fontsize == 0)
            fontsize = 12;
        if (slideshow == 0)

```

5

10

15

20

25

30

35

40

45

50

55

APPENDIX A

Jukebox.java

7

8

```

    showing = tk.getImage(new
        initCodeBase, "streaminfo.class");
    loading = tk.getImage(new
        initCodeBase, "streamheader.class");
    } catch (MalformedURLException e) {
        showing = null;
        loading = null;
    }

    /* Construct the selection box using the given
     * parameters
     */
    if (mediatype.equals("live") || mediatype.equals("liveMML-1")) {
        selbox = new JukeboxSelection(initial);
    } else {
        if (showSlides)
            selbox = new JukeboxSelection(mediadir, tracks,
                titles, slides,
                slidewidth, slidheight);
        else
            selbox = new JukeboxSelection(mediadir, tracks,
                titles);
    }

    /* Construct the controller and pass the selection box
     * to it.
     */
    controller = new JukeboxController(server, port, selbox,
        mediatype, this, database,
        isDetachable, aboutimg);

    /* Tell the selection box who is observing it.
     */
    selbox.setObserver(controller);

    /* Layout the GUI components. AWT sucks.
     */
    DirPanel = new Panel();
    DirPanel.setLayout(new BorderLayout());
    setColors(DirPanel, background, foreground);
    setColors(titles, background, foreground);
    setColors(tracks, fontName, fontStyle, fontColor);
    DirPanel.add(DirPanel, selbox);
    DirPanel.add("South", controller);
    add(DirPanel);

    public void start() {
        if (!isDetached)
            controller.resume();
    }

    public void stop() {
        if (!isDetached)
            controller.pause();
    }

    public void destroy() {
        if (!isDetached)
            detachFrame.close();
        controller.abort();
    }

    /* Detach the GUI and bring it up in a separate window
     * so that the user can control the jukebox separately
     * from the browser.
     */
    public void detach() {
        isDetached = true;
        removeDirPanel();
        detachFrame = new javax.swing.JFrame("Java Jukebox", this,
            DirPanel, iconimg);
        controller.makeAttachable();
    }

    /* Attach the GUI back to the page in the browser.
     */
    public void attach() {
        isDetached = false;
        detachFrame.close();
        add(DirPanel);
        controller.makeDetachable();
        paintAll(getGraphics());
    }

    /* Stop the audio and
     * attach the GUI back to the page in the browser.
     */
    public void close() {
        controller.stop();
        attach();
    }

    public boolean isDetached() {
        return isDetached;
    }

    private void setColors(DirPanel p, String background, String foreground) {
        Color c;
        c = getColors(background);
        if (c != null) {
            p.setBackground(c);
        }
        c = getColors(foreground);
        if (c != null) {
            p.setForeground(c);
        }
    }

    private Color getColors(String name) {
        if (name == null)
            return null;
        if (name.equalsIgnoreCase("black"))
            return Color.black;
        else if (name.equalsIgnoreCase("blue"))
            return Color.blue;
        else if (name.equalsIgnoreCase("cyan"))
            return Color.cyan;
        else if (name.equalsIgnoreCase("darkGray"))
            return Color.darkGray;
    }

```

APPENDIX A

Jukebox.java

```

9
    return Color.darkGray;
    else if (name.equalsIgnoreCase("gray"))
        return Color.gray;
    else if (name.equalsIgnoreCase("green"))
        return Color.green;
    else if (name.equalsIgnoreCase("lightGray"))
        return Color.lightGray;
    else if (name.equalsIgnoreCase("magenta"))
        return Color.magenta;
    else if (name.equalsIgnoreCase("orange"))
        return Color.orange;
    else if (name.equalsIgnoreCase("pink"))
        return Color.pink;
    else if (name.equalsIgnoreCase("red"))
        return Color.red;
    else if (name.equalsIgnoreCase("white"))
        return Color.white;
    else if (name.equalsIgnoreCase("yellow"))
        return Color.yellow;
    else {
        StringTokenizer t = new StringTokenizer(name, " ");
        if (t.countTokens() == 3) {
            try {
                int red = Integer.parseInt(t.nextToken());
                int green = Integer.parseInt(t.nextToken());
                int blue = Integer.parseInt(t.nextToken());
                return new Color(red, green, blue);
            } catch (Exception e) {
                return null;
            }
        }
        return null;
    }
}

private void setPoints(Panel p, String name, String style, int size) {
    int fontStyle;
    if (style.equalsIgnoreCase("italic"))
        fontStyle = Font.ITALIC;
    else if (style.equalsIgnoreCase("bold"))
        fontStyle = Font.BOLD;
    else if (style.equalsIgnoreCase("bolditalic"))
        fontStyle = Font.BOLD + Font.ITALIC;
    else
        fontStyle = Font.PLAIN;
    p.setFont(new Font(name, fontStyle, size));
}

```

5

10

15

20

25

30

35

40

45

50

55

APPENDIX B DetachedFrame.java

```

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000

```

Claims

1. A process comprising the steps of:
5 implementing a detachable interface; and
 modifying a non-detachable applet to become a detachable applet.
2. A process according to claim 1 wherein the step of implementing comprises the step of:
 modifying the class definition of said non-detachable applet to include a detachable interface.
- 10 3. A process according to claim 2 wherein the step of modifying comprises the step of:
 adding a set of generic methods for implementing said detachable interface
4. A process according to claim 3 further comprising the step of:
15 modifying any of said set of generic methods to suit the desired look-and-feel of said detachable applet.
5. A process according to step 3 wherein said step of adding comprises the steps of:
 adding a first method for placing said detachable applet into a detached state; and
20 adding a second method for placing said detachable applet if in the detached state back to an attached state.
6. A process according to claim 5 further comprising the step of:
 adding a third method for toggling between said states.
- 25 7. A process according to claim 5 further comprising the step of:
 adding a fourth method for disposing completely said detachable applet while in the detached state.
8. A process for controlling the behavior of an applet exclusive of application constraints comprising the steps of:
30 detaching said applet from said application, said applet continuing to utilize a virtual machine of said application
 to execute applet instructions;
 displaying a detached window to render visually said applet; and
 enabling the modification of visual properties of said detached window.
- 35 9. A process according to claim 8 wherein the step of detaching comprises the steps of:
 activating a user interface element to detach applet while graphically constrained by said application; and
 calling a Detach method for executing a set of instructions pursuant to completing said steps of detaching,
40 displaying and enabling.
10. A process according to claim 8 further comprising the step of attaching said applet into said application.
11. A process according to claim 10 wherein the step of attaching comprises the steps of:
45 calling an Attach method;
 closing said detached window; and
 redrawing said applet into said application.
12. A process according to claim 9 wherein the step of calling a detach method initiates the steps of:
50 instantiating a new frame;
 removing components of said applet from said application;
 adding said removed components to said new frame;
 mapping said detached window onto a display device; and
55 painting said added components onto said display device, said painting to occur within the mapped detached
 window.
13. A graphical user interface system for controlling an applet comprising:

- a desktop defined by an operating environment;
 a application window visually displayed as an overlay on said desktop, said application window displaying and visually constraining said applet while said applet is in an attached state; and
 a detached window running directly over said desktop, said detached window being displayed on said desktop only while said applet is in a detached state, said detached state removing said applet from being visually constrained and displayed in said application window.
- 5
14. A graphical user interface system according to claim 13 wherein said detached window includes a user interface element for enabling said applet to be placed in the attached state.
- 10
15. A graphical user interface system according to claim 14 wherein said application window includes a user interface element for enabling said applet to be placed in the detached state.
16. A graphical user interface according to claim 14 wherein said detached window is closed when said applet is placed in the attached state.
- 15
17. A graphical user interface system according to claim 13 wherein said applet is launched initially in the attached state.
- 20
18. A graphical user interface system according to claim 13 wherein said applet is launched initially in the detached state.
- 25
19. A computer-readable medium having stored thereon applet code interpretable by an application, said applet code including sequences of instructions which, when executed by a processor, cause said processor to perform the steps of:
- detaching said applet from said application, said applet continuing to utilize a virtual machine of said application to facilitate execution of said sequence of instructions by said processor;
 displaying a detached window to render visually said detached applet; and
 enabling the modification of visual properties of said detached window.
- 30
20. A computer software product having applet code interpretable by an application, said computer software product distributed to a processor, said applet code including sequences of instructions which, when executed by said processor, cause said processor to perform the steps of:
- 35
- detaching said applet from said application, said applet continuing to utilize a virtual machine of said application to facilitate execution of said sequence of instructions by said processor;
 displaying a detached window to render visually said detached applet; and
 enabling the modification of visual properties of said detached window.
- 40
21. A signal representative of applet code interpretable by an application, said applet code including sequences of instructions which, when executed by a processor, cause said processor to perform the steps of:
 detaching said applet from said application, said applet continuing to utilize a virtual machine of said application to facilitate execution of said sequence of instructions by said processor;
- 45
- displaying a detached window to render visually said detached applet; and
 enabling the modification of visual properties of said detached window.
- 50
22. A method of storing data on a recording medium, the method comprises storing data comprising applet code interpretable by an application, said applet code including sequences of instructions which, when executed by said processor, cause said processor to perform the steps of:
- detaching said applet from said application, said applet continuing to utilize a virtual machine of said application to facilitate execution of said sequence of instructions by said processor;
 displaying a detached window to render visually said detached applet; and
 enabling the modification of visual properties of said detached window.
- 55
23. A signal according to claim 21, wherein the signal is recorded on a recording medium.

24. A signal according to claim 23, wherein the recording medium comprises a magnetic disc, a magnetic tape, an optical disc or an electronic memory device.

5

10

15

20

25

30

35

40

45

50

55




FIGURE 1




FIGURE 2




FIGURE 3




FIGURE 4




FIGURE 5




FIGURE 6




FIGURE 7